



由 Autodesk 教育版产品制作

- Instruction:
1. Type: Film to Film
 2. Operating Voltage: 5~7 V
 3. Response Time: $\le 10\text{ms}$
 4. Storage Temperature: $-20\text{ }^{\circ}\text{C} \sim 70\text{ }^{\circ}\text{C}$
 5. Operation Temperature/Humidity: $-10\text{ }^{\circ}\text{C} \sim 60\text{ }^{\circ}\text{C} / 20\% \sim 90\% \text{RH}$
 6. Withstanding Life: $>10,000,000$ Times, 250gf Force;
 7. Writting Life: $>1,000,000$ Times 250gf Force;
 8. Densort Material: PPO+PIH

9. Film Thickness: 0.188mm
10. Film Thickness: 0.188mm
11. Light transmittance: $\ge 70\%$
12. Force: 100g or Less
13. Linearity: $\le 1.5\%$
14. Insulation: $\ge 20\text{M } \Omega$
15. Surface Bandwidth: $\ge 8\text{f (open:11)}$
16. 未标注公差为 $\pm 0.3\text{mm}$

CJ156A4K05		UNIT:	mm
MODEL NO.		TOLERANCE:	± 0.3
DRAWN:		SCALE:	1:1
DATE:	1b/10/1b	REV:	
VERSION:	1.0		